

Lawrence Livermore National Laboratory

LLNL Plutonium Facility Criticality Alarm System

November 10, 2010



Soon Kim and Edward Orham
Nuclear Criticality Safety Division, Nuclear Operations Directorate

Lawrence Livermore National Laboratory, P. O. Box 808, Livermore, CA 94551

This work performed under the auspices of the U.S. Department of Energy by
Lawrence Livermore National Laboratory under Contract DE-AC52-07NA27344


UCRL-PRES-460671

LLNL Pu Facility CAS System

- *Gamma ray detector based system,*
- *Current system went into service in 1995 after a rigorous factory acceptance test and a three month burn-in test after installation,*
- *In compliance with ANSI/ANS 8.3 requirements,*
- *28 detectors currently in use in the RMA.*



CAS System



Designed on

Three Subassemblies,


- *Radiation Detection*
- *Evacuation Alarm Module*
- *Power Supply*

CAS Detectors



- *Sensitive to gamma rays,*
- *Uses a plastic scintillator to convert radiation to photons,*
- *Located in the Radiation Material Area*
- *Requires 2 or more detectors in alarm to generate an evacuation alarm*
- *Analog meter box provides continuous radiation readings*

Radiation Detection




- *Off-the-Shelf equipment,*
- *Equipment was purchased from Nuclear Measurement Corporation,*
- *26 detectors was initially installed*
- *28 active detector/detector modules,*
- *Operating range is from 0.1 mR/hr to 100 R/hr, setpoint is 100mR/h*
- *Threshold and alarm set points are set by the keypad on the module,*
- *Redundant PLC (SLC500) monitoring of all inputs.*

Evacuation Alarm



- *LLNL designed and fabricated,*
- *Relay Logic controlled,*
- *Displays system conditions,*
- *Latches alarm indications on until manual reset is performed,*
- *Horns (106) and strobes (8) are off-the-shelf Federal devices.*
- *Horns operates on 450-500 hertz with a modulated tone of 4-5 hertz, 92 – 115 db*

Power Supply



- *Provides power to Radiation Detection and EAM subassemblies,*
- *24 volt DC system,*
- *Redundant battery charger/power supply,*
- *Parallel battery banks*



CAS Testing

- *Perform a channel check weekly using the built-in light source,*
- *Perform a semiannual criticality radiation detector electronic check of each detector, including alarm setting and readout,*
- *Verify the alarm response of the CAS semiannually with two or more criticality radiation detectors at high alarm,*
- *Verify semiannually that all criticality horns and strobe lights are functional,*
- *Perform a battery load test and a visual inspection semiannually,*
- *Source check all active criticality radiation detectors semiannually.*



Detector Placement Analysis

Analytical Calculations:

- *Determine the minimum fission yields for 20 rad in free air at the distance of 2 m from the reacting material within 60 sec,*
- *Calculate dose rates at the gamma detectors,
(set point: 100 mR/hr)*

In-Situ Measurements Using Co-60 Source:

- *Determine the response of the heads,*
- *Confirm the estimated response of the detectors.*



Minimum Fission Yield

For the absorbed dose of 20 rad at a distance of 2 m in air in 60 sec, $20 \text{ (rad)} = f \text{ (fissions)} \times \Sigma [y_i \text{ (rad/fission)}]$

System Type	Neutron Dose, y_1 (rad/fission)	Secondary Gamma Dose, y_2 (rad/fission)	Prompt Gamma Dose, y_3 (rad/fission)	Fission Product Gamma Dose, y_4 (rad/fission)	Total (rad/fission) Σy_i	Minimum Fission Yield (fissions), f
Pu Metal	1.822×10^{-15}	1.633×10^{-18}	6.703×10^{-16}	6.703×10^{-16}	3.164×10^{-15}	6.321×10^{15}
U Metal	1.092×10^{-15}	8.633×10^{-19}	3.810×10^{-16}	3.810×10^{-16}	1.855×10^{-15}	1.078×10^{16}
Pu Moderated	7.260×10^{-16}	1.151×10^{-18}	5.117×10^{-15}	5.117×10^{-15}	1.096×10^{-14}	1.825×10^{15}
U Moderated	5.729×10^{-16}	1.078×10^{-18}	4.008×10^{-15}	4.008×10^{-15}	8.590×10^{-15}	2.328×10^{15}



Detector Response to the Minimum Fission Yield

- *Calculated gamma ray flux based on the minimum fission yield,*
- *Source placed in each room maximizing the distance from the detectors,*
- *28 detectors placed on walls throughout the RMA,*
- *Confirmed by Co-60 Measurements.*



12-rad Boundary Analysis

- *Bounding fission yield estimated based on facility activities,*
 - *Pu, U, and/or Np in the form of metal alloy and oxide*
- *Historical accidents for bare and reflected metal systems*
 - *Total fissions ranged from 3×10^{15} to 3.7×10^{17}*
- *For reflected bulk metal and metal pieces or solid fines, such as powder that are moderated and reflected, 1×10^{18} fissions in a single burst is assessed to be bounding reference value and is believed to be very conservative (DOE-HDBK-3010-94)*



Three Incidents that Caused False Alarms

- *July 2004, After returning CAS to normal operation condition, it was discovered that various detector modules on start up acted differently.*
- *June 2005, In preparing for CAS testing, the tester activated the CAS audible/visual output,*
- *March 2010, In modifying the building paging system in the RMA, an audible alarm was generated which sounded like the criticality alarm audible output.*



Summary

- *In-Situ Co-60 measurements determine the response of the heads as well as confirm the estimated response of the CAS detectors for the minimum accident of concern and the 12-rad boundary analyses,*
- *LLNL CAS actively monitors and collects dosimetry data for assessing background radiation levels and for monitoring post-accident conditions remotely,*
- *Planned to remain active after completion of de-inventory of security category I/II materials in the near future.*

